

FOOD SERVICE PRODUCTS				
Product Code	Product Description	Rebate/Unit	Page #	
402004	Fryer: Electric	\$650.00/Vat	7	
402005	Fryer: Gas	\$749.00/Vat	<u>7</u>	
402026	Convection Oven: Electric	\$350.00/Oven	-	
402027	Convection Oven: Gas	\$500.00/Oven	<u>7</u>	
402029	Gas Rack Oven: Double	\$2,000.00/Unit	<u>7</u>	
402032	Kitchen Ventilation Control: Retrofit	\$1,500.00/Fan HP	0	
402033	Kitchen Ventilation Control: New	\$750.00/Fan HP	<u>8</u>	
402135	Steam Cooker: Electric	\$1,600.00 /Steamer	-	
402136	Steam Cooker: Gas	\$2,000.00/Steamer	<u>7</u>	
402160	Glass-Door Reach-in Freezer 15-29 ft ³	\$100.00/Unit		
402161	Glass-Door Reach-in Freezer 30-49 ft ³	\$165.00/Unit	<u>9</u>	
402159	Glass-Door Reach-in Freezer 50 ft ³ and over	\$250.00/Unit		
462971	Griddle: Electric	\$200.00/Linear Foot		
462972	Griddle: Gas	\$100.00/Linear Foot		
465296	Griddle: Electric - New	\$200.00/Linear Foot	<u>9</u>	
465297	Griddle: Gas - New	\$100.00/Linear Foot		
463498	Combination Oven < 15 Pans: Electric	\$1,200.00/Oven		
463499	Combination Oven 15-28 Pans: Electric	\$1,200.00/Oven		
463500	Combination Oven > 28 Pans: Electric	\$3,500.00/Oven	10	
463501	Combination Oven < 15 Pans: Gas	\$1,100.00/Oven	<u>10</u>	
463502	Combination Oven 15 - 28 Pans: Gas	\$1,000.00/Oven		
463503	Combination Oven > 28 Pans: Gas	\$2,000.00/Oven		
464053	Ice Machine SCU < 110 lbs./day: New	\$50/Unit		
464054	Ice Machine SCU < 110 lbs./day: Retrofit	\$50/UIIIL		
464055	Ice Machine SCU 110 – 200 lbs./day: New	\$150.00/Unit		
464056	Ice Machine SCU 110 – 200 lbs./day: Retrofit	\$150.00/01110		
464057	Ice Machine SCU > 200 lbs./day: New	\$200.00/Unit	11	
464058	Ice Machine SCU > 200 lbs./day: Retrofit	\$200.00/Unit	<u>11</u>	
464059	Ice Machine IMH < 300 lbs./day: New	\$75/Unit		
464060	Ice Machine IMH < 300 lbs./day: Retrofit	\$/5/UIIIL		
464061	Ice Machine IMH 300 – 799 lbs./day: New	\$125.00/Unit		
464062	Ice Machine IMH 300 – 799 lbs./day: Retrofit	\$123.00/ UIIIL		



464063	Ice Machine IMH 800 – 1499 lbs./day: New	\$200.00/Unit	
464064	Ice Machine IMH 800 – 1499 lbs./day: Retrofit	\$200.00/Unit	
464065	Ice Machine IMH > 1500 lbs./day: New	¢200/Uni+	
464066	Ice Machine IMH > 1500 lbs./day: Retrofit	\$300/Unit	_
464067	Ice Machine RCU < 988 lbs./day: New	¢200/Umi#	
464068	Ice Machine RCU < 988 lbs./day: Retrofit	\$300/Unit	<u>11</u>
464069	Ice Machine RCU ≥ 988 lbs./day: New	¢400.00/Unit	
464070	Ice Machine RCU ≥ 988 lbs./day: Retrofit	\$400.00/Unit	

	REFRIGERATION PRODUCTS				
Product Code	Production Description	Rebate/Unit	Page #		
402152	Refrigeration Display Case with Doors: Low Temp	\$75.00/Linear Foot	12		
402153	Refrigeration Display Case with Doors: Medium Temp	\$75.00/Lilleal Foot	<u>13</u>		
465293	Anti-Sweat Heater Controls: Low Temp	¢2F 00/Linear Foot	12		
465295	Anti-Sweat Heater Controls: Medium Temp	\$25.00/Linear Foot	<u>13</u>		
467192	Saturated Discharge Controls: Air-cooled	\$29.00/Capacity Ton			
467194	Saturated Discharge Controls with Variable speed fan: Air-cooled	\$200.00/Capacity Ton	14		
467196	Saturated Discharge Controls: Evap-cooled	\$29.00/Capacity Ton	<u>14</u>		
467198	Saturated Discharge Controls with Variable speed fan: Evap-cooled	\$200.00/Capacity Ton			
467200	Saturated Suction Controls: Air-cooled	\$20,00/Canacity Ton	1.4		
467202	Saturated Suction Controls: Evap-cooled	\$29.00/Capacity Ton	<u>14</u>		
467205	High Efficiency Ultra Low Temp Freezer (24 to 29 ft.³): New	¢600.00/Unit	15		
467206	High Efficiency Ultra Low Temp Freezer (24 to 29 ft.³): Retrofit	\$600.00/Unit	<u>15</u>		

NATURAL GAS PRODUCTS				
Product Code	Product Description	Rebate/Unit	Page #	
402421	Ozone Laundry System	\$39.00/lb.	<u>17</u>	
465438	30 Gallon MedDraw Storage Water Heater, UEF ≥ 0.64: Retrofit			
465440	40 Gallon MedDraw Storage Water Heater, UEF ≥ 0.64: Retrofit	\$2.00/ Cap-kBtuh	17	
465441	40 Gallon HiDraw Storage Water Heater, UEF ≥ 0.68: Retrofit	72.00, 00p Notan		



465442	50 Gallon MedDraw Storage Water Heater, UEF ≥ 0.64: Retrofit		
465443	50 Gallon HiDraw Storage Water Heater, UEF ≥ 0.68: Retrofit	\$2.00/ Cap-kBtuh	
465474	Large Storage Water Heater – TE > 0.83 ≤ 0.90	¢2.00/ Can libturk	10
463333	Large Storage Water Heater – TE > 0.90	\$2.00/ Cap-kBtuh	<u>18</u>
466583	Large Instantaneous Heaters, >200 kBtu/hr, 80% TE	¢0.50/Com liBturk	40
466585	Large Instantaneous Heaters, >200 kBtu/hr, 90% TE	\$0.50/Cap-kBtuh	<u>18</u>
466586	Process Boiler-Hot Water – 85% CE	¢0.50/Com liPtick	10
466588	Process Boiler-Hot Water – 90% CE	\$0.50/Cap-kBtuh	<u>19</u>
466957	Steam Trap Replacement	\$100.00/Unit	<u>19</u>

	PIPE/PIPE FITTING INSULATION PRODUCTS		
Product Code	Product Description	Rebate/Unit	Page #
466896	1" Pipe Insulation: Hot Water Pipe ≤ 1" diameter: Indoor		
466842	1" Pipe Insulation: Hot Water Pipe, ≤ 1" diameter: Outdoor		
466897	1" Pipe Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Indoor	¢2.00/Linear Foot	
466843	1" Pipe Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Outdoor	\$3.00/Linear Foot	
466898	1" Pipe Insulation: Hot Water Pipe, > 4" diameter: Indoor		
466844	1" Pipe Insulation: Hot Water Pipe, > 4" diameter: Outdoor		
466923	1" Fitting Insulation: Hot Water Pipe \leq 1" diameter: Indoor	¢7.00/Fach	
466869	1" Fitting Insulation: Hot Water Pipe ≤ 1" diameter: Outdoor		
466924	1" Fitting Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Indoor	¢10.00/Fach	
466870	1" Fitting Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Outdoor	\$10.00/Each	21
466925	1" Fitting Insulation: Hot Water Pipe, > 4" diameter: Indoor	¢12.00/50ch	<u>21</u>
466871	1" Fitting Insulation: Hot Water Pipe, > 4" diameter: Outdoor	\$12.00/Each	
466899	1" Pipe Insulation: ≤ 15 psig Steam Pipe, ≤ 1" diameter: Indoor		
466845	1" Pipe Insulation: ≤ 15 psig Steam Pipe, ≤ 1" diameter: Outdoor		
466900	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor		
466846	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	ć2 00 /l in any Foot	
466901	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Indoor	\$3.00/Linear Foot	
466847	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Outdoor		
466902	1" Pipe Insulation: > 15 psig Steam Pipe, ≤ 1" diameter: Indoor		
466848	1" Pipe Insulation: > 15 psig Steam Pipe, ≤ 1" diameter: Outdoor		



466903	1" Pipe Insulation: > 15 psig Steam Pipe, > 1", < 4" diameter: Indoor		
466849	1" Pipe Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	\$3.00/Linear Foot	
466904	1" Pipe Insulation: > 15 psig Steam Pipe, > 4" diameter: Indoor	¢2.00/linear Fact	
466850	1" Pipe Insulation: > 15 psig Steam Pipe, > 4" diameter: Outdoor	\$3.00/Linear Foot	
466926	1" Fitting Insulation: ≤ 15 psig Steam Pipe ≤ 1" diameter: Indoor	¢42.00/5k	
466872	1" Fitting Insulation: \leq 15 psig Steam Pipe \leq 1" diameter: Outdoor	\$12.00/Each	
466927	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor	¢15.00/555b	
466873	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	\$15.00/Each	
466928	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Indoor	620.00/Fach	21
466874	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Outdoor	\$30.00/Each	<u>21</u>
466929	1" Fitting Insulation: > 15 psig Steam Pipe ≤ 1" diameter: Indoor	¢12.00/Fach	
466875	1" Fitting Insulation: > 15 psig Steam Pipe \leq 1" diameter: Outdoor	\$12.00/Each	
466930	1" Fitting Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor	¢15 00/52ch	
466876	1" Fitting Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	\$15.00/Each	
466931	1" Fitting Insulation: > 15 psig Steam Pipe, > 4" diameter: Indoor	\$20.00/Each	
466877	1" Fitting Insulation: > 15 psig Steam Pipe, > 4" diameter: Outdoor	\$30.00/Each	

	OTHER TECHNOLOGY PRODUCTS		
Product Code	Product Description	Rebate/Unit	Page #
465336	Greenhouse Heat Curtains *Pre-Inspection Required*	\$0.20/Square Foot	<u>22</u>
463521	Pool Cover - Outdoor	\$1.00/Square Foot	<u>23</u>



GENERAL REQUIREMENTS

- Customers must have an active San Diego Gas & Electric® (SDG&E) commercial, industrial or agricultural electric account if applying for an electric measure and an SDG&E gas account if applying for a gas measure.
- Customer must adhere to all program requirements. Additionally, customer must provide all information when a 'Data Collection Requirements' section is present.
- Applied products must be installed and operational before the rebate application is submitted to SDG&E.
- All rebates apply toward the purchase of new or replacement energy-efficient equipment. New, used or rebuilt
 equipment is not eligible.
- Customer must provide proof that product(s) meet the energy efficiency requirements.
- It is the responsibility of the customer to ensure the equipment to be installed adheres to all state, local and national building codes or ordinances, as well as the manufacturer's requirements.
- Several products offered through the Energy Efficiency Business Rebates program are provided at no cost or at a discount for qualified customers through SDG&E's Business Energy Solutions program. Customers with a monthly electrical demand less than 200 kW may participate and should visit sdge.com/BES or call our Energy Savings Center at 1-800-644-6133 for details.



FOOD SERVICE/REFRIGERATION REQUIREMENTS & DEFINITIONS

- All foodservice equipment must be listed on <u>caenergywise.com</u> to qualify or <u>www.energystar.gov/products</u>, unless otherwise noted in the product requirement section.
- Medium temperature refers to refrigerated space temperatures between 1°F and 35°F. Low temperature covers temperatures below 0°F.

ASHRAE

The American Society of Heating, Refrigerating and Air-Conditioning Engineers.

ASTM

American Society for Testing and Materials.

CEE

Consortium for Energy Efficiency. CEE Tier specifications are available at http://www.cee1.org.

ENERGY STAR

ENERGY STAR specifications are available at: www.energystar.gov/cfs.



FOOD SERVICE PRODUCTS

COMMERCIAL FRYER

Requirements:

- The commercial natural gas and electric fryer must meet ENERGY STAR® specifications for energy efficiency or must be listed on <u>caenergywise.com</u> to qualify.
- Multiple vat configurations are paid per qualifying vat.
- Fryer must also meet the tested requirements below:

Commercial Fryer Table

Product Code	Description	Cooking Efficiency	Idle Energy Rate	Rebate/Unit
402004	Electric Fryer (vat width <18 inches)	80%	≤ 1,000 W	\$650.00/Vat
402005	Gas Fryer (vat width <18 inches)	50%	≤ 9,000 Btu/h	\$749.00/Vat

COMMERCIAL CONVECTION OVEN

Requirements:

• Must be listed in the California Energy Commission database and meet ENERGY STAR® specifications for energy efficiency or be listed on caenergywise.com.

Commercial Convection Table

Product Code	Description	Rebate/Unit
402026	Commercial Electric Convection Oven	\$350.00/Oven
402027	Commercial Gas Convection Oven	\$500.00/Oven

COMMERCIAL RACK OVEN (NATURAL GAS)

Requirements:

• The commercial natural gas rack oven must meet ENERGY STAR® specifications for energy efficiency or must be listed on caenergywise.com to qualify.

Commercial Rack Oven (Natural Gas) Table

Product Code	Description	Rebate/Unit
402029	Commercial Gas Rack Oven –Double	\$2,000.00/Unit

COMMERCIAL STEAM COOKER

Requirements:

• The commercial natural gas and electric steam cooker must meet ENERGY STAR® specifications for energy efficiency or must be listed on <u>caenergywise.com</u> to qualify.

Commercial Steam Cooker Table

Product Code	Description	Rebate/Unit
402135	Steam Cooker: Electric	\$1,600.00/Steamer
402136	Steam Cooker: Gas	\$2,000.00/Steamer



COMMERCIAL KITCHEN VENTILATION CONTROL

Requirements:

- The control system must be listed on California Energy Wise and meet the criteria below to qualify.
 - o California Energy Wise: http://caenergywise.com/rebates
- The new commercial kitchen exhaust hood control system must be installed in an existing or a new dedicated commercial kitchen exhaust hood and makeup air system.
- Installation must include temperature sensor(s) in the hood exhaust collar or within the hood, and/or an optic sensor on the end of the hood or within the hood that senses cooking conditions.
- The control system must be used in conjunction with a variable-speed drive (VSD) on the fan motor.
- Installations in a new exhaust hood must have a total kitchen hood airflow ≤ 5,000 cfm.
- If installed in an existing exhaust hood > 5,000 cfm, the existing hood must have been installed before July 1, 2014 due to code requirements.
- To comply with SB 454, applicant <u>must use a licensed contractor</u>, as appropriate, and follow applicable
 permitting requirements for this installation. Both the customer certification and the contractor certification
 in section 10 of the Energy Efficiency Business Rebates application must be completed for this HVAC related
 product.

Data Collection Requirements:

• Must provide verification of total exhaust cfm controlled by the new or existing kitchen hood.

Restrictions:

- Used or rebuilt controls are not eligible.
- Systems with total kitchen hood airflow > 5,000 cfm installed after July 1, 2014 are not eligible.

Commercial Kitchen Ventilation Control Table

Product Code	Description	Rebate/Unit
402032	Kitchen Ventilation Control: Retrofit	\$1,500.00/Fan HP
402033	Kitchen Ventilation Control: New	\$750.00/Fan HP



COMMERCIAL GLASS DOOR FREEZER

Requirements:

- The refrigeration system shall be built-in (packaged). Cases with remote refrigeration systems do not qualify.
- Used or rebuilt equipment is not eligible.
- Qualifying models must be listed on <u>caenergywise.com</u> and meet ENERGY STAR® specifications for energy efficiency as listed in Table below.

Maximum Daily Energy Consumption Requirements

Product Volume (in cubic feet)	Freezer (Glass Door)
15 ≤ V < 30 ft3	≤ 0.232V + 2.36 kWh/day
30 ≤ V < 50 ft3	≤ 0.232V + 2.30 KWII/Udy
50 ≤ V ft3	

V = Internal volume in ft₃ (cubic foot)

Restrictions:

- Used or rebuilt equipment are not eligible.
- Units with remote refrigeration systems do not qualify.

Commercial Glass Door Freezer Table

Product Code	Description	Rebate/Unit
402160	Glass-Door Reach-in Freezer 15-29 ft ³	\$100.00/Unit
402161	Glass-Door Reach-in Freezer 30-49 ft ³	\$165.00/Unit
402159	Glass-Door Reach-in Freezer 50 ft ³ and over	\$250.00/Unit

COMMERCIAL GRIDDLE

Requirements:

• The commercial natural gas and electric griddle must meet ENERGY STAR® specifications for energy efficiency or must be listed on caenergywise.com to qualify.

Restrictions:

- Double-sided griddles are not eligible.
- Used or rebuilt equipment are not eligible.

Commercial Griddle Table

Product Code	Description	Rebate/Unit
462971	Griddle: Electric	\$200.00/Linear Foot
462972	Griddle: Gas	\$100.00/Linear Foot
465296	Griddle: Electric - New	\$200.00/Linear Foot
465297	Griddle: Gas - New	\$100.00/Linear Foot



COMMERCIAL COMBINATION OVEN

Requirements:

- The commercial electric and natural gas combination oven must meet ENERGY STAR® specifications for energy efficiency or must be listed on caenergywise.com to qualify.
- Must meet the tested efficiency requirements listed in the table below.

Restrictions:

• Used or rebuilt equipment are not eligible.

Efficiency Requirements

		Cooking Ene	rgy Efficiency	Idle Energy Rate		Production Capacity (lb/hr)	
Туре	Capacity (pans)	Oven Mode	Steam Mode	Oven Mode	Steam Mode	Oven Mode	Steam Mode
	< 15			2,000 W	5,000 W	100	120
Electric	15-28	≥ 70%	≥ 50%	2,500 W	6,000 W	125	200
	> 28			4,000 W	9,000 W	325	400
	< 15			8,000 Btu/hr	15,000 Btu/hr	100	120
Gas	15-28	≥ 44%	≥ 38%	10,000 Btu/hr	18,000 Btu/hr	125	200
	> 28			16,000 Btu/hr	28,000 Btu/hr	325	400

Commercial Combination Oven Table

Product Code	Description and Required Efficiency	Rebate/Unit		
463498	Combination Oven < 15 Pans: Electric	\$1,200.00/Oven		
463499	Combination Oven 15-28 Pans: Electric	\$1,200.00/Oven		
463500	Combination Oven > 28 Pans: Electric	\$3,500.00/Oven		
463501	Combination Oven < 15 Pans: Gas	\$1,100.00/Oven		
463502	Combination Oven 15 - 28 Pans: Gas	\$1,000.00/Oven		
463503	Combination Oven > 28 Pans: Gas	\$2,000.00/Oven		



COMMERICAL ICE MACHINES

Requirements:

- Qualifying models must meet Qualified Ice Maker specifications listed on <u>caenergywise.com</u>.
- Only air-cooled machines (self-contained, icemaker heads, or remote condensing) are eligible.
- To qualify the entire Air Conditioning, Heat and Refrigeration Institute (AHRI) tested ice-making system must be purchased. Remote machines must be purchased with qualifying remote condenser or remote condenser/compressor unit.
- Models must meet Energy Star Version 3.0 specifications listed below.

Restrictions:

- Used or rebuilt equipment are not eligible.
- Water-cooled ice machines do not qualify.

ENERGY STAR V3.0 Program Requirements for Batch Type Automatic Commercial Ice Makers

Equipment Type	Daily Ice Harvest Rate (Ibs. ice/24 hrs.)	Maximum Daily Energy Use (kWh/100 lbs. ice)	Maximum Daily Potable Water Use Limit (gal/100 lbs. ice)
	H < 300	9.20 – 0.01134 x H	
Ice Maker Head	300 ≤ H < 800	6.49 – 0.0023 x H	20
(IMH)	800 ≤ H ≤ 1500	5.11 – 0.00058 x H	20
	1500 ≤ H ≤ 4000	4.24	
Remote Condensing Unit	H < 988	7.17 – 0.00308 x H	20
(RCU)	988 ≤ H ≤ 4000	4.13	20
Self-Contained Unit	H < 110	12.57 – 0.0399 x H	
	110 ≤ H < 200	10.56 – 0.0215 x H	25
(SCU)	200 ≤ H ≤ 4000	6.25	

ENERGY STAR V3.0 Program Requirements for Continuous Type Automatic Commercial Ice Makers

Equipment Type	Daily Ice Harvest Rate (Ibs. ice/24 hrs.)	Maximum Daily Energy Use (kWh/100 lbs. ice)	Maximum Daily Potable Water Use Limit (gal/100 lbs. ice)
	H < 310	7.90 – 0.005409 x H	
Ice Maker Head	310 ≤ H < 820	7.08 – 0.002752 x H	15
(IMH)	820 ≤ H ≤ 4000	4.82	15
	H < 800	7.76 – 0.00464 x H	
Remote Condensing Unit	800 ≤ H ≤ 4000	4.05	15
(RCU)	H < 200	12.37 – 0.0261 x H	15
Self-Contained Unit	200 ≤ H < 700	8.24 – 0.005429 x H	
	700 ≤ H ≤ 4000	4.44	15
(SCU)	H < 310	7.90 – 0.005409 x H	



Commercial Ice Machines Table				
Product Code	Description (Ice Harvest Rate Capacity)	Rebate/Unit		
464053	Ice Machine SCU < 110 lbs./day: New	¢50/Umit		
464054	Ice Machine SCU < 110 lbs./day: Retrofit	\$50/Unit		
464055	Ice Machine SCU 110 – 200 lbs./day: New	¢150.00/Uzit		
464056	Ice Machine SCU 110 – 200 lbs./day: Retrofit	\$150.00/Unit		
464057	Ice Machine SCU > 200 lbs./day: New	\$300.00/Unit		
464058	Ice Machine SCU > 200 lbs./day: Retrofit	\$200.00/Unit		
464059	Ice Machine IMH < 300 lbs./day: New	¢7F/Unit		
464060	Ice Machine IMH < 300 lbs./day: Retrofit	\$75/Unit		
464061	Ice Machine IMH 300 – 799 lbs./day: New	\$13F 00/Unit		
464062	Ice Machine IMH 300 – 799 lbs./day: Retrofit	\$125.00/Unit		
464063	Ice Machine IMH 800 – 1499 lbs./day: New	\$300.00/Unit		
464064	Ice Machine IMH 800 – 1499 lbs./day: Retrofit	\$200.00/Unit		
464065	Ice Machine IMH > 1500 lbs./day: New	\$200/Unit		
464066	Ice Machine IMH > 1500 lbs./day: Retrofit	\$300/Unit		
464067	Ice Machine RCU < 988 lbs./day: New	Ć200/Umit		
464068	Ice Machine RCU < 988 lbs./day: Retrofit	\$300/Unit		
464069	Ice Machine RCU ≥ 988 lbs./day: New	\$400.00/11¤i+		
464070	Ice Machine RCU ≥ 988 lbs./day: Retrofit	\$400.00/Unit		



REFRIGERATION PRODUCTS

REFRIGERATION DISPLAY CASE WITH DOORS

Requirements:

- This measure is applicable for supermarkets and grocery stores with stand-alone and/or multiplex compressor racks that provide refrigeration to remote display cases and walk-in coolers/freezers. Additionally, they have both medium-temperature and low temperature open multi-deck refrigeration cases.
- Must replace an existing, open, multi-deck display case with a new reach-in unit with doors, electronically commutated motor (ECM) evaporator fan(s), and LED lighting.
- Medium-temperature cases must have no heat in the door. Heat is allowed in the frames of medium temperature cases.
- Low-temperature case door and frame heaters combined may not consume more than 50 W/ft of case length.
- The new case length must be less than or equal to the original case length.
- This measure is only for display cases served by a remote refrigeration system.

Restrictions:

- Specialty deli cases, custom coolers/freezers, and walk-in boxes with reach-in doors are not eligible.
- Refurbished cases are not eligible unless compliant with the 2012 Federal Efficiency Standards (see Code Requirements).
- Display case replacements that are part of large-scale store remodels and any new construction projects should be revised to be custom measures. Large-scale remodels are defined as any project involving 50% of the linear feet of refrigerated casework or 32 linear feet of casework replacements, whichever is less.

Refrigeration Display Case with Doors Table

Product Code	Description	Rebate/Unit
402152	Refrigeration Display Case with Doors: Low Temp	\$75.00/Linear Foot
402153	Refrigeration Display Case with Doors: Medium Temp	\$75.00/Linear Foot

ANTI-SWEAT HEATER CONTROLS

Requirements:

- This product is applicable for any existing commercial building type, including (but not limited to) supermarkets, grocery stores, hotels, restaurants, and convenience stores.
- To qualify, the display case must be equipped with humidity-sensing controls that reduce the amount of power supplied to the heaters as the store dew point (DP) temperature decreases.
- Typically, power reduction occurs when relative humidity levels reach 55% and lower. Power reduction should decrease by at least 2% for every percentage the humidity falls below 55%.
- Equivalent technologies that can reduce or turn off ASHs based on the amount of condensation formed on the inner glass pane may also qualify.

Data Collection Requirements:

Must provide the vintage of the building and the refrigeration multiplex system.

Restrictions:

• This product cannot be used in conjunction with product code 402152 and 402153.

Anti-Sweat Heater Controls Table

Product Code	Description	Rebate/Unit
465293	Anti-Sweat Heater Controls: Low Temp	\$25.00/Linear Foot
465295	Anti-Sweat Heater Controls: Medium Temp	\$25.00/Linear Foot



SATURATED DISCHARGE CONTROLS

Requirements:

- Controls must be added to an existing air-cooled or evaporative-cooled multiplex refrigeration system that has a fixed Saturated Condensing Temperature (SCT) control.
- Controls must float head pressure down to a lower pressure when conditions permit (i.e., changes control
 from fixed set point to floating set point), reducing the SCT setpoint to a minimum of 70°F based on ambient
 conditions.
- The new SCT setpoint must be ambient following by controlling condenser fans with variable-speed drives or by staging condenser fans.
- For air-cooled systems, the SCT must be controlled to follow +12°F temperature difference or lower.
- For evaporative-cooled systems, the SCT must be controlled to follow a +17°F temperature difference or lower.
- If back-flood controls are present, the back-flood control setpoint must be 68°F or lower.
- Rebate is based on the design cooling load (tons), which accounts for connected display cases, walk-in coolers and freezers, and cooled storage and prep areas only.

Data Collection Requirements:

• Must provide the vintage of the building and the refrigeration multiplex system.

Restrictions:

- Projects that only reprogram a controller are not eligible.
- Sub-cooler loads and air conditioning loads are not eligible.
- Multiplex systems majorly upgraded or installed after July 1, 2014 do not qualify since the Title-24 code mandates floating controls.

Saturated Discharge Controls Table

Product Code	Description	Rebate/Unit
467192	Saturated Discharge Controls: Air-cooled	\$29.00/Capacity Ton
467194	Saturated Discharge Controls with Variable speed fan: Air-cooled	\$200.00/Capacity Ton
467196	Saturated Discharge Controls: Evap-cooled	\$29.00/Capacity Ton
467198	Saturated Discharge Controls with Variable speed fan: Evap-cooled	\$200.00/Capacity Ton

SATURATED SUCTION CONTROLS

Requirements:

- Controls must be added to an existing air-cooled or evaporative-cooled multiplex refrigeration system that has a fixed Saturated Suction Temperature (SST) control.
- Controls must raise suction pressure during periods of low fixture loads to the highest point that can still
 maintain setpoint temperatures at monitored cases on the suction circuit.
- The maximum suction setpoint is 5°F above the design temperature. The minimum suction setpoint should be the same as the existing refrigeration system.
- Rebate is based on the design cooling load (tons), which accounts for connected display cases, walk-in coolers and freezers, and cooled storage and prep areas only.

Data Collection Requirements:

• Must provide the vintage of the building and the refrigeration multiplex system.

Restrictions:

- Projects that only reprogram a controller are not eligible.
- Sub-cooler loads and air conditioning loads are not eligible.
- Multiplex systems majorly upgraded or installed after July 1, 2014 do not qualify since the Title-24 code mandates floating controls.

Saturated Suction Controls Table

Product Code	Description	Rebate/Unit
467200	Saturated Suction Controls: Air-cooled	¢20.00/Canacity Ton
467202	Saturated Suction Controls: Evap-cooled	\$29.00/Capacity Ton



HIGH EFFICIENCY ULTRA LOW TEMP FREEZERS

Requirements:

- Qualifying freezers must be listed on Energy Star to be eligible, or the maximum daily energy consumption (MDEC) of an Ultra Low Temp freezer at -75 °C (-103 °F) is 0.55 kWh/day/ft³
- Volume must be \geq 24 ft³ \leq 29 ft³.
- Freezer must be capable of maintaining temperatures down between -70 °C and -80 °C (-94 °F and -112 °F)
- The rebate is only applicable for the existing building types: Education University, Health/Medical –
 Hospital, Manufacturing Biotech, and Manufacturing Pharmaceuticals.

High Efficiency Ultra Low Freezers Table

Product Code	Description	Rebate/Unit
467205	High Efficiency Ultra Low Temp Freezer (24 to 29 ft.3): New	\$600.00/Unit
467206	High Efficiency Ultra Low Temp Freezer (24 to 29 ft.3): Retrofit	\$600.00/OHIL



NATURAL GAS REQUIREMENTS & DEFINITIONS

The California Energy Commission (CEC) and/or Gas Appliance Manufacturers Association (GAMA) equipment efficiency listed ratings prevail over all submitted technical documentation, unless otherwise approved.

BUBBLE DIFFUSION

A method of inserting ozone into water by continuously bubbling ozone directly into the sump of the washer throughout the wash cycle.

COMBUSTION EFFICIENCY (CE)

100 times (1 - energy lost to flue) divided by input energy.

Cap-kBtuh

1,000 Btuh.

THERMAL EFFICIENCY (TE)

100 times useful energy output divided by input energy.

TOTAL WASHER CAPACITY

Refers to rated capacity of installed and operating washing machine units that will be connected to the ozone laundry system(s).

VENTURI INJECTION

A method of inserting ozone into water using very high pressure directly into the cold-water supply line leading to the washer.



NATURAL GAS PRODUCTS

OZONE LAUNDRY SYSTEM

Requirements:

- Customer must have a natural gas-fired boiler or natural gas water heater that supplies hot water to the onpremise laundry equipment.
- The washing capacity of each washing machine must be rated at 200 pounds or less.
- The ozone laundry system(s) must be a new purchased product and installed with a new or existing commercia I washing machine(s) at a hotel/motel, health center, nursing home, or correctional facility.
- The ozone laundry system(s) must transfer ozone into the water with either the venturi injection or bubble diff usion process.
 - o Venturi Injection: Ozone is injected into the cold-water supply line leading to the washer.
 - Bubble Diffusion: Ozone is continuously injected directly into the sump of the washer throughout each step of the wash cycle.
- Rebate is per pound of total onsite washer capacity.

Restrictions:

- Laundry systems equipped with tunnel washers are not eligible.
- Multifamily facilities do not qualify.

Ozone Laundry System Table

Product Code	Description	Rebate/Unit
402424	One me Levine du l'Eventeure	\$39.00/lb.
402421	Ozone Laundry System	Washing Machine Capacity

SMALL STORAGE WATER HEATER

Requirements:

- New energy efficient gas storage water heater must replace a standard efficiency gas storage water heater
- Only storage water heaters as defined by the California Energy Commission qualify:
 - Must be used primarily for domestic hot water
 - Have an input rating of less than 4,000 Btu per hour per gallon of stored water
- New water heater must also meet the efficiency requirements and input ratings as shown in the table below.

Restrictions:

• Water heaters or hot water boilers used for space conditioning, industrial (process) end-use applications, pools, or spas do not qualify.

Small Storage Water Heater Table

Product Code	Description	Required Efficiency	Input Rating	Rebate/Unit
465438	30 Gallon MedDraw Storage Water Heater: Retrofit	UEF ≥ 0.64		
465440	40 Gallon MedDraw Storage Water Heater: Retrofit	UEF 2 0.64		
465441	40 Gallon HiDraw Storage Water Heater: Retrofit	UEF ≥ 0.68	≤ 75 kBtu/hr	\$2.00/ Cap-kBtuh
465442	50 Gallon MedDraw Storage Water Heater: Retrofit	UEF ≥ 0.64		
465443	50 Gallon HiDraw Storage Water Heater: Retrofit	UEF ≥ 0.68		



LARGE STORAGE WATER HEATER

Requirements:

- New energy efficient gas storage water heater must replace a standard efficiency gas storage water heater
- Only storage water heaters as defined by the California Energy Commission qualify:
 - Must be used primarily for domestic hot water
 - o Have an input rating of less than 4,000 Btu per hour per gallon of stored water
- New water heater must also meet the efficiency requirements and input ratings as shown in the table below.

Restrictions:

• Water heaters or hot water boilers used for space conditioning, industrial (process) end-use applications, pools, or spas do not qualify.

Large Storage Water Heater Table

Product Code	Description	Required Efficiency	Input Rating	Rebate/Unit
465474	Large Storage Water Heater – TE > 0.83	TE > 0.83 ≤ 0.90	> 75 kD+/br	\$2.00/ Cap-kBtuh
463333	Large Storage Water Heater – TE > 0.90	TE > 0.90	> 75 kBtu/hr	32.00/ Cap-RBtuil

LARGE INSTANTANEOUS (TANKLESS) WATER HEATER

Requirements:

- New energy efficient gas large instantaneous water heater must replace a standard efficiency gas water heater.
- Only large instantaneous water heaters as defined by the California Energy Commission qualify:
 - Be used primarily for domestic hot water
 - o Provide hot water only when there is a hot water draw from the end use.
 - Have an input rating of at least 4,000 Btu/hr per gallon of stored water.
- Applicant must provide proof of the tankless nature of the water heater (e.g., manufacturer equipment specification sheets).
- Large instantaneous water heaters must meet efficiency requirements based on size shown in Table below.

Restrictions:

- Water heaters or hot water boilers used for space conditioning, industrial (process) end-use applications, pools, or spas do not qualify.
- Cannot be used to supply hot water to a circulation loop without an intermediary hot water storage tank.

Instantaneous (Tankless) Water Heater Table

Product Code	Description	Required Efficiency	Input Rating	Rebate/Unit
466583	Large Instantaneous Heaters, >200 kBtu/hr, 80% TE	TE ≥ 0.80	> 200 kB+u/b*	\$0.50/Cap-kBtuh
466585	Large Instantaneous Heaters, >200 kBtu/hr, 90% TE	TE ≥ 0.90	≥ 200 kBtu/hr	30.30/Cap-kbtuii



PROCESS BOILER

Requirements:

- Rebate is available to all existing commercial, agriculture, and industrial (nonresidential) buildings.
 Additionally, industrial end-use customers who manufacture a sellable product (NAICS codes 31-33) qualify for the rebate.
- Boilers must meet efficiency requirements as shown in Table below.

Restrictions:

- Boilers primarily used for space heating, domestic hot water, pools, or spas, and is not eligible for domestic hot water or space heating do not qualify.
- New construction installations are not eligible.

Process Boiler Table

Product Code	Description	Input Rating	Required Efficiency	Rebate/Unit
466586	Process Boiler-Hot Water – 85% CE	< 200 000 kB+u /bs	CE ≥ 85%	CO FO/Con kB+ub
466588	Process Boiler-Hot Water – 90% CE	< 200,000 kBtu/hr	CE ≥ 90%	\$0.50/Cap-kBtuh

STEAM TRAPS

Requirements:

- Must be a commercial facility that operates 12-24 hours per day large commercial facilities with a steam plant operating a steam boiler for 12 to 24 hours per day.
- Steam traps must replace one-to-one an existing failed or older steam traps.
- Steam traps designed for any pipe size are eligible.
- For each steam trap being replaced must provide steam trap manufacturer, model number, specification sheet, paid purchase receipt with tax and proof of shipping.
- Must provide operating pressure of steam system, and construction style (mechanical, thermostatic, or thermodynamic).
- May be asked to verify the location of the replaced steam trap(s) in steam loop.

Restrictions:

- Small commercial facilities which operate their steam systems less than 12 hours per day are not eligible to receive the rebate.
- New construction installations are not eligible.

Steam Traps Table

Product Code	Description & Technical Requirements	Rebate/Unit
	Large Commercial Operating System 12-24 hrs./day	
466957	Dry cleaners excluded.	\$100.00/Unit
	Not available for Industrial and Agricultural Applications.	



PIPE/PIPE FITTING INSULATION PRODUCTS

PIPE/PIPE FITTING INSULATION

Requirements:

- A minimum of one inch of pipe insulation must be added to an existing bare commercial or industrial steel or copper pipe or pipe fitting (elbows, tees, valves, unions, flanges, reducers, bushings, couplings, etc.).
- The pipe must have a minimum diameter of ½-inch and transfer hot water, low-pressure steam, or medium-pressure steam directly from gas-fired equipment, and the fluid type must be indicated. If the fluid is steam, the pressure of the steam must also be indicated.
- Acceptable types of insulation for hot water pipes include elastomeric foam rubber, polyethylene foam, UV-resistant polyethylene foam, and rigid polyurethane foam.
- Acceptable types of insulation for steam pipes include silicone foam rubber, melamine foam, rigid urethane-based foam, cellular glass, rigid fiberglass, and rigid mineral wool.

Data Collection Requirements:

- Length of insulation to be installed with each pipe size must be indicated on the application.
- Hours of operation must be indicated on the application.
- Manufacturer specification sheet must be submitted with the application.

Restrictions:

- Insulation required by California Building Energy Efficiency Standards (Title 24) or employee safety laws (Occupational Safety and Health Administration, OSHA) does not qualify.
- Replacement of damaged (existing) insulation does not qualify.
- New construction installations are not eligible.
- Residential installations are not eligible.



	Pipe/Pipe Fitting Insulation Table	
Product Code	Description	Rebate/Unit
466896	1" Pipe Insulation: Hot Water Pipe ≤ 1" diameter: Indoor	
466842	1" Pipe Insulation: Hot Water Pipe, ≤ 1" diameter: Outdoor	
466897	1" Pipe Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Indoor	\$3.00/Linear Foot
466843	1" Pipe Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Outdoor	53.00/Linear Foot
466898	1" Pipe Insulation: Hot Water Pipe, > 4" diameter: Indoor	
466844	1" Pipe Insulation: Hot Water Pipe, > 4" diameter: Outdoor	
466923	1" Fitting Insulation: Hot Water Pipe < 1" diameter: Indoor	67.00/Fash
466869	1" Fitting Insulation: Hot Water Pipe ≤ 1" diameter: Outdoor	\$7.00/Each
466924	1" Fitting Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Indoor	¢10.00/Fash
466870	1" Fitting Insulation: Hot Water Pipe, > 1", ≤ 4" diameter: Outdoor	\$10.00/Each
466925	1" Fitting Insulation: Hot Water Pipe, > 4" diameter: Indoor	¢12.00/5h
466871	1" Fitting Insulation: Hot Water Pipe, > 4" diameter: Outdoor	\$12.00/Each
466899	1" Pipe Insulation: ≤ 15 psig Steam Pipe, ≤ 1" diameter: Indoor	
466845	1" Pipe Insulation: ≤ 15 psig Steam Pipe, ≤ 1" diameter: Outdoor	
466900	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor	
466846	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	
466901	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Indoor	
466847	1" Pipe Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Outdoor	¢2 00/Linear Foot
466902	1" Pipe Insulation: > 15 psig Steam Pipe, ≤ 1" diameter: Indoor	\$3.00/Linear Foot
466848	1" Pipe Insulation: > 15 psig Steam Pipe, ≤ 1" diameter: Outdoor	
466903	1" Pipe Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor	
466849	1" Pipe Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	
466904	1" Pipe Insulation: > 15 psig Steam Pipe, > 4" diameter: Indoor	
466850	1" Pipe Insulation: > 15 psig Steam Pipe, > 4" diameter: Outdoor	
466926	1" Fitting Insulation: ≤ 15 psig Steam Pipe ≤ 1" diameter: Indoor	¢12.00/Fach
466872	1" Fitting Insulation: ≤ 15 psig Steam Pipe ≤ 1" diameter: Outdoor	\$12.00/Each
466927	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor	¢15 00/50ch
466873	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	\$15.00/Each
466928	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Indoor	¢20.00/Fach
466874	1" Fitting Insulation: ≤ 15 psig Steam Pipe, > 4" diameter: Outdoor	\$30.00/Each
466929	1" Fitting Insulation: > 15 psig Steam Pipe ≤ 1" diameter: Indoor	¢12.00/50ch
466875	1" Fitting Insulation: > 15 psig Steam Pipe ≤ 1" diameter: Outdoor	\$12.00/Each
466930	1" Fitting Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Indoor	¢1E 00/Fach
466876	1" Fitting Insulation: > 15 psig Steam Pipe, > 1", ≤ 4" diameter: Outdoor	\$15.00/Each
466931	1" Fitting Insulation: > 15 psig Steam Pipe, > 4" diameter: Indoor	¢20.00/50ch
466877	1" Fitting Insulation: > 15 psig Steam Pipe, > 4" diameter: Outdoor	\$30.00/Each



OTHER TECHNOLOGY PRODUCTS

GREENHOUSE HEAT CURTAINS

Requirements:

- **Pre-inspection required!** Applicant must submit an online application at sdge.com/NLRebates to schedule a pre-inspection.
- Rebate is available for existing agricultural or commercial greenhouses for the primary purpose of the production of nursery products, horticultural specialties, or ornamental products.
- Must be a single-layer interior curtain installed for heat retention
- Must be installed in an existing gas-heated greenhouse facility
- The facility must be a greenhouse with the primary purpose of agricultural use.
- The heat curtain must be a new curtain installed where none previously existed or a new curtain that is replacing an existing curtain that is no longer functional.
- The heat curtain must be installed above the conditioned area where the gas heat source provides hot air to plant and seed species.
- The heat curtain must have a natural gas savings rating that meets or exceeds 40%.
- The heat curtain must have a warranty/product life of five years.
- The installation must allow the curtain to be automatically or manually moved into place.

Restrictions:

- The square footage of the new heat curtain cannot exceed the square footage of the greenhouse floor.
- Overhang and overlap of curtain material cannot be included in the square footage calculation

Greenhouse Heat Curtains Table

Product Code	Description	Rebate/Unit
465336	Greenhouse Heat Curtains	\$0.20/Square Foot



POOL COVER - OUTDOOR

Requirements:

- Eligible facilities are:
 - Existing schools/colleges (educational institutions)
 - o City (municipal) recreational centers
 - Home owner associations (e.g., condominiums with common pools)
 - Private/health clubs
 - Multifamily residences (apartment buildings)
- Outdoor and indoor heated swimming pools that do not already have a pool cover qualify for the rebate.

 Additionally, if the facility has an existing pool cover the pool cover must no longer be in use, has reached the end of its useful life, and is no longer effective to qualify for the rebate.
- The pool must be heated with natural gas.
- The cover must have 1/8" thick (L), high-density polyethylene foam of thermal conductivity (K) Factor 0.25 Btu/ft²-Hr-°F/inch (based upon the ASTM D2326 standard, withdrawn).
- The new pool cover must cover at least 95% of the pool
- Proof of minimum five-year warranty (any combination of manufacturers and/or extended applies).
- Proof of cover thickness and K factor (found on the manufacturer specification sheet)
- Olympic size pools must have a storage reel system either manual or automatic winding and are subject to inspection.
- Rebate is applicable to installed pool cover; per pool only
- Rebate is based on the square footage of the pool area
- 100% post inspection

Restrictions:

New construction installations are not eligible.

Pool Cover Table

Product Code	Description	Efficiency Requirements	Rebate/Unit
463521	Outdoor Pool Cover	R value ≥ 0.5 ft ² – hr °F/Btuh	\$1.00/square foot

Olympic Size – Defined as having a straight length of 25 yards, and a minimum eight lanes whose centerline width must be 2.5 yards (4,592 ft² minimum) R Value – Thermal Resistance non-dimensional value found using the following formula (R value = t/k). Where t = thickness of pool cover in inches; and k is the pool cover's thermal conductivity factor with units of BTU/ft² – hr. - 'F/inch. Customer's goal is to find a pool cover whose R value \geq 0.5 ft² – hr. - 'F/Btu. Sample Calculation: R = t/k = (1/8")/0.25 BTU ft²-hr. F/Btu.



The selection, purchase, and ownership of goods and services are the sole responsibility of the customer. SDG&E makes no representations as to the safety, reliability, and/or efficiency of goods and services selected. SDG&E makes no warranty, whether express or implied, including warranty of merchantability or fitness for any particular purpose, use or application of selected goods and services. The program is funded by California utility customers and administered by SDG&E under the auspices of the California Public Utilities Commission (CPUC). Program funds will be made on a first-come, first-served basis until program funds are no longer available. This program may be modified or terminated without prior notice. The selection, purchase and ownership of goods and services are the sole responsibility of the

The web site links contained herein are provided for information purposes only. SDG&E does not endorse these web sites, or any goods or services of- offered thereon. Particularly, SDG&E has not verified the privacy policies applicable to these web sites, or determined what actions will be taken by third parties regarding the privacy of visitors. In no event, shall SDG&E be responsible for any third-party web site policies or actions.